

Product Information Sheet

ADVANTAGES

- Liquid oxidizing biocide for use in membrane systems and a variety of water treatment applications
- Broad spectrum and fast reacting to prevent growth of bacteria, fungi, algae and slime
- Effective over a wide pH range, with highest efficacy below pH 8.5
- Does not react with ammonia or amines, and does not contribute to nitrosamine formation
- Fully biodegradable and environmentally friendly
- Formulated to be used in direct contact with reverse osmosis, nanofiltration and ultrafiltration membranes
- Certified by NSF to NSF/ANSI Standard 60

TYPICAL PROPERTIES

Appearance	Clear colorless liquid
Odor	Vinegar odor
Solubility in water	Complete

PACKAGING

5 gallon pails, 55 gallon non-returnable plastic drums, 275 gallon totes.

AWC® D-615P

Stabilized Peracetic Acid 15%

SAFETY & HANDLING

Causes severe skin burns and eye damage. Wear at least chemical resistant gloves and eye protection, face shield, and chemical resistant garments when handling, moving or using this product. Harmful if swallowed, absorbed through the skin, or inhaled. Wash thoroughly with soap and water after handling, and before eating or drinking. For more information, see the Safety Data Sheet provided with this product.

CHEMICAL FEEDING AND CONTROL

Dose 13 - 33 ppm of AWC D-615P continuously into the Reverse Osmosis or Ultrafiltration System. For occasional intermittent feed, do not exceed 620 ppm of AWC D-615P.

For sanitation, use only after removing all foulant from membranes by high and low pH cleaning. Circulate a 0.5% solution for up to 4 hours, and make sure to open and close valves to ensure that all parts in fully in contact with the disinfectant solution.



P: +1.813.246.5448 // E: info@membranechemicals.com // www.membranechemicals.com