

Product Information Sheet

ADVANTAGES

- Low foaming liquid formulation designed for use as a high pH cleaner of polyamide thin film composite membranes.
- Penetrates biofilms and organic foulants and disperses clays and colloidal silica.
- Supports the cleaning of sulfate, fluoride and silicate scales.
- Effectively dissolves iron hydroxide deposits
- Compatible with all Thin Film Composite R.O. membranes from all major membrane suppliers
- Certified by NSF to NSF/ANSI Standard 60 for use in potable systems

TYPICAL PROPERTIES

Appearance	Dark brown liquid
Odor	Characteristic
Solubility in water	Complete

PACKAGING

5 gallon pails, 55 gallon non-returnable plastic drums and 275 gallon totes

AWC® C-241

High pH Liquid Cleaner - Low Foaming

SAFETY & HANDLING

Store in cool, dry and well ventilated area. Keep containers closed. Wash contaminated clothes before re-use. Wash thoroughly after handling. For more information, see the Safety Data Sheet provided with this product.

CHEMICAL FEEDING AND CONTROL

The cleaning solution should be prepared using RO permeate that is free of residual chlorine or other oxidizing agents. Add 2 gallons of AWC C-241 to every 100 gallons of water (2 % solution). Adjust the pH in the range 11–12. Send the first 20% of the solution to drain to displace any residual feed water in the system, and then begin circulation. Do not exceed pressures, temperatures and flow rates recommended by the membrane manufacturer. Cleaning efficacy can be further improved by heating the cleaning solution and alternately circulating the solution for 30 -60 minutes and then soaking the membranes for 30 - 60 minutes. This should be repeated for a total of 4 – 6 hours of total contact time. The pH range should be monitored every 30 minutes throughout the cleaning. When pH drops below the desired range, it should be adjusted by adding more AWC C-241.



P: +1.813.246.5448 // E: info@membranechemicals.com // www.membranechemicals.com