

Product Information Sheet

ADVANTAGES

- Cost-effective liquid formulation designed for use as a low pH cleaner of polyamide thin film composite membrane surfaces
- Removes inorganic carbonate, phosphate and sulfate scalants as well as metal oxides
- Contains a synergistic blend of cleaners and scale removal agents for a thorough cleaning of the membrane
- May eliminate the need for repeat cleanings in cases of severe scaling
- Compatible with all Thin Film Composite R.O. membranes from all major membrane suppliers
- Certified by NSF to NSF/ANSI Standard 60

TYPICAL PROPERTIES

Appearance	Colorless to light yellow liquid
Odor	Essentially no odor
Solubility in water	Complete
pH (1% solution)	1.85 ± 0.3
Specific Gravity	1.08 ± 0.05

PACKAGING

5 gallon pails, 55 gallon non-returnable plastic drums and 275 gallon totes

AWC® C-231

Low pH Membrane Cleaning Compound

SAFETY & HANDLING

Store in cool, dry and well ventilated area. Keep containers closed. Wash contaminated clothes before re-use. Wash thoroughly after handling. For more information, see the Safety Data Sheet provided with this product.

CHEMICAL FEEDING AND CONTROL

The cleaning solution should be prepared using potable water that is free of residual chlorine or other oxidizing agents. Add 17 lbs of AWC C-231 to every 100 gallons of water (2% solution). Adjust the pH to <2 by adding more chemical if needed. Recirculate the cleaning solution throughout the system, after redirecting the first 20% of the solution to drain. Do not exceed pressures, temperatures and flow rates recommended by the membrane manufacturer. Cleaning efficacy can be further improved by heating the cleaning solution. Monitor the pH range periodically throughout the cleaning. When pH increases above the desired range, it should be adjusted by adding more AWC C-231.



P: +1.813.246.5448 // E: info@membranechemicals.com // www.membranechemicals.com